

## Specifications

Rollers:	4" diameter synthetic dough rollers complete with nylon scrapers
Bearings:	All sealed heavy duty ball bearings
Sprockets:	Keyway and setscrews attached with a totally enclosed roller chain drive
Motor:	3/4 HP, heavy duty TEFC motor, 1ph/115/230V/60Hz
Belt:	FDA approved polyester
Safety system:	Infeed guard bar with automatic shut off
Pressure plates:	1 per machine (Specify size)

## Features

- Gentle spring loaded rollers
- 4" Diameter rollers c/w nylon scrapers
- Fully adjustable side guides
- Hand feed or use under a bread plant
- Infeed safety guard with auto-matic shut off
- Totally enclosed chain and sprocket drive
- Produce up to 3,600 pcs/hr.

## Options

Flat pressure plates:	FDA fabric covered—35" long, curved plates available
Motor:	6 options available

# GEMINI

Since 1972

## Bread & Roll Moulder 860 and 860L



## Technical Data

Model	Dimensions inches			Total Capacity lbs.	Belt Width inches	Ship Weight lbs.	Electrical					
	Width	Depth	Height				volts	ph	Hz	HP	amps	Plug
860	56"	23"	52"	0.5 oz to 4 lbs.	18"	600	115	1	60	75	10.8	Plug: NEMA 5-15
860L	56"	29"	52"	0.5 oz to 4 lbs.	24"	630	115	1	60	75	10.8	Plug: NEMA 5-15

In an effort to consistently upgrade our products, we reserve the right to change specifications and dimensions without notice.

# GEMINI

Creative Technology and Service for the Baking Industry

**Gemini Bakery Equipment Company**  
 9990 Gantry Road  
 Philadelphia, PA 19115—1002  
 (215) 673-3520 Fax: (215) 673-3944  
 sales@geminibe.com  
 www.geminibe.com



Item No. Gem-C250058 August 2005